



Pin	Connection
1 ( 3 )	Collector VT2
2 ( 4 )	Base VT2
3 ( 5 )	Emitter VT2
4 ( 8 )	Collector VT1
5 ( 7 )	Base VT1
6 ( 6 )	Emitter VT1

(numbering of tare leads is indicated in brackets)

## Electrical Characteristics

Parametr	Conditions	T <sub>A</sub>	Min	Max	Units
Collector Reverse Current	U <sub>CB</sub> = 20 V	+25°C	-	10	nA
		-45°C	-	10	
		+85°C	-	1000	
Reverse Emitter Current	U <sub>BE</sub> = 4 V	+25°C	-	20	nA
		-45°C	-	20	
		+85°C	-	500	
Initial Collector Current	U <sub>CE</sub> = 15 V, R <sub>B</sub> = 10 <sup>4</sup> Ω	+25°C	-	20	nA
		-45°C	-	20	
		+85°C	-	1000	
Leakage Current between transistors	U <sub>T1T20</sub> = 25 V	+25°C	-	10	nA
		-45°C	-	10	
		+85°C	-	300	
Static Forward Current Transfer Ratio in a Common-Emitter Circuit in Large Signal Mode	U <sub>CB</sub> = 5V, f= 50 Hz, τ <sub>u</sub> = 2 ms I <sub>E</sub> = 1 mA	+25°C	30	90	
		-45°C	13	90	
		+85°C	30	180	
	U <sub>CB</sub> = 5V, f= 50 Hz, τ <sub>u</sub> = 2 ms I <sub>E</sub> = 0,05 mA	+25°C	50	-	
		-45°C	30	-	
		+85°C	60	-	
Ratio of Static Forward Current Transfer Coefficients in Common Emitter Circuit in Large Signal Mode	U <sub>CB</sub> = 5 V, f= 50 Hz, τ <sub>u</sub> = 2 ms I <sub>E</sub> = 1 mA	+25°C	0,9	-	
		-45°C	0,8	-	
		+85°C	0,8	-	
	U <sub>CB</sub> = 5 V, f= 50 Hz, τ <sub>u</sub> = 2 ms I <sub>E</sub> = 0,05 mA	+25°C	0,88	-	
		-45°C	0,85	-	
		+85°C	0,85	-	
High Frequency Current Transfer Ratio Module	U <sub>CB</sub> = 5V, I <sub>E</sub> =3 mA, f= 10 <sup>8</sup> Hz	+25°C	2,5	-	
Forward voltage difference modulus emitter-base	U <sub>CB</sub> = 5V, I <sub>E</sub> =1 mA	+25°C	-	2,5	mV
Absolute change in modulus of emitter-base voltage difference	U <sub>CB</sub> =1 V, I <sub>E</sub> = 1mA	-45°C ÷ + 85 °C	-	2	mV
collector junction capacitance	U <sub>CB</sub> = 5V, f=10 <sup>7</sup> Hz	+25°C	-	3	pF
Emitter junction capacitance	U <sub>BE</sub> = 1V, f=10 <sup>7</sup> Hz	+25°C	-	4	pF
Forward voltage emitter-base transistors	U <sub>CE</sub> =5V, I <sub>E</sub> =1mA	+25°C	0,55	0,75	V

Microcircuits are made under supervision of Quality Department, checked and there correspond specification  
 Quality Dept. stamp